

EN362 DMM Connectors Product List Abbreviations : AV = Anti Vibration Screwgate, CB = Captive Bar, B = Basic Connector, T = Termination Connector, H = HMS Connector, K = Klettersteig Connector, X = Oval Connector

Aluminium Connectors

Product	CatNo	EN	TZ	22	362:	ANSI	ASSE/	CAN/	NFPA	Strength	Gate	Opening
					2004		2359.12	2239.12	1983:	kN		mm
Aero Offset D	A372 / A372AV	B	B	-	-	-	-	-	25	17		
Aero HMS	A362 / CB	B&H	B/T	-	-	-	-	-	25	19		
	A362AV / CBAV	B&H	B/T	-	-	-	-	-	25	17		
	A363 / CB	B&H	B/T	-	-	-	-	-	25	17		
Sentinel	A367 / CB	B&H	B/T	-	-	-	-	-	25	17		
	A362 / A262AV	B	B	-	-	-	-	-	24	20		
	A263	B&H	B	-	-	-	-	-	24	17		
	A267	B&H	B	-	-	-	-	-	24	17		
Revolver	A272 / A272AV	B	B	-	-	-	-	-	24	16		
	A273	B	B	-	-	-	-	-	24	15		
	A277	B	B	-	-	-	-	-	24	15		
Shadow	A302 / A302AV	B	B	-	-	-	-	-	24	18		
	A303	B	B	-	-	-	-	-	24	17		
	A307	B	B	-	-	-	-	-	24	17		
Phantom	A312	B	B	-	-	-	-	-	24	15		
Phantom HMS	A573	H	B	-	-	-	-	-	25	19		
	A577	H	B	-	-	-	-	-	25	19		
Ultra O	A322 / CB	B	B/T	-	-	-	-	-	25	22		
	A322AV / CBAV	B	B/T	-	-	-	-	-	25	22		
	A323 / CB	B	B	-	-	-	-	-	25	19		
	A324	B	B	-	-	-	-	-	25	19		
	A327 / CB	B	B/T	-	-	-	-	-	25	19		
Ultra D	A332 / CB	B	B/T	-	-	-	-	-	30	22		
	A332AV / CBAV	B	B/T	-	-	-	-	-	30	22		
	A333 / CB	B	B	-	-	-	-	-	30	22		
	A333ANSI / CBANSI	B	B/T	2009	2016	-	-	-	30	21		
	A334 / CB	B	B/T	-	-	-	-	-	30	20		
	A337 / CB	B	B/T	-	-	-	-	-	30	22		
	A337ANSI / CBANSI	B	B/T	2009	2016	-	-	-	30	16		
Rhino	A542AV	B&H	B	-	-	-	-	-	27	20		
	A543	B&H	B	-	-	-	-	-	27	19		
	A547	B&H	B	-	-	-	-	-	27	19		
	A113	-	-	-	-	-	-	-	22	42		
	A734	-	T	1992	-	-	-	-	23	52		
	A734OL / TA733OLCR	-	T	1992	-	-	-	-	23	52		
	A734ANSI Ultima	-	T	2009	2016	-	-	-	38	53		
	A763	-	T	1992	-	-	-	-	22	18		
Zodiac	A822 / CB	B	B/T	-	-	-	-	-	32	18		
	A822AV / CBAV	B	B/T	-	-	-	-	-	32	18		
	A823 / CB	B	B/T	-	-	-	-	-	32	18		
	A827 / CB	B	B/T	-	-	-	-	-	32	18		
	A842 / CB	B	B/T	-	-	-	-	-	30	26		
	A842AV / CBAV	B	B/T	-	-	-	-	-	30	26		
	NFPA / A843 / CB	B&K	B/T	-	-	-	-	-	Class T	30	21	
	A843ANSI / CBANSI	B	B/T	2009	2016	-	-	-	30	21		
	A844 / CB	B&K	B/T	-	-	-	-	-	30	22		
	NFPA / A847 / CB	B&K	B/T	-	-	-	-	-	Class T	30	24	
	A847ANSI / CBANSI	B	B/T	2009	2016	-	-	-	30	21		
Belay Master 2	A872 / CB	B&H	B/T	-	-	-	-	-	25	24		
	A872AV / CBAV	B&H	B/T	-	-	-	-	-	25	24		
	A892 / CB	B&H	B/T	-	-	-	-	-	25	25		
	A892AV / CBAV	B&H	B/T	-	-	-	-	-	25	25		
	A893 / CB	B&H	B/T	-	-	-	-	-	25	23		
	A897 / CB	B&H	B/T	-	-	-	-	-	25	23		
30 kN HD Boa	A902 / CB	B&H	B/T	-	-	-	-	-	30	25		
	A902AV / CBAV	B&H	B/T	-	-	-	-	-	30	25		
	A903 / CB	B&H	B/T	-	-	-	-	-	30	21		
	A903ANSI / CBANSI	B	B/T	2009	2016	-	-	-	30	19		
	A904 / CB	B&H	B/T	-	-	-	-	-	30	19		
	A907 / CB	B&H	B/T	-	-	-	-	-	30	23		
	A907ANSI / CBANSI	B	B/T	2009	2016	-	-	-	30	19		
	A912 / A912AV	-	-	-	-	-	-	-	30	24		
	A913	-	-	-	-	-	-	-	30	23		
	A913ANSI	-	-	-	-	-	-	-	30	19		
	A917	-	-	-	-	-	-	-	30	23		
	A917ANSI	-	-	-	-	-	-	-	30	19		
	A98K21	-	-	-	-	-	-	-	25	21		
	A98K31	-	-	-	-	-	-	-	25	18		
	A98K31ANSI	-	-	-	-	-	-	-	25	20		
	A98K71	-	-	-	-	-	-	-	25	20		
	A98K71ANSI	-	-	-	-	-	-	-	25	20		
Ceros	A562 / CB	B&H&T	T/B&T	-	-	-	-	-	25	15		
	A563 / CB	B&H&T	T/B&T	-	-	-	-	-	25	19		
	A567 / CB	B&H&T	T/B&T	-	-	-	-	-	25	19		
	A592 / CB	B&X/T	B/T	-	-	-	-	-	24	16		
	A593 / CB	B&X/T	B/T	-	-	-	-	-	24	15		
	A597 / CB	B&X/T	B/T	-	-	-	-	-	24	15		

Steel Connectors

Small Scaffold Shadow	C113	-	T	-	-	-	-	-	45	38	
	C302/CB	B	B	-	-	-	-	-	40	17	
	C303/CB	B	B/T	-	-	-	-	-	40	15	
	C307/CB	B	B/T	-	-	-	-	-	40	15	
Oval	C322/CB	B&X	B/T	-	-	-	-	-	30	19	
	C323/CB	B&X	B/T	-	-	-	-	-	30	19	
	C327/CB	B&X	B/T	-	-	-	-	-	30	19	
10 mm Equal	C412 / CB	B	B/T	-	-	-	-	-	30	15	
	C413 / CB	B	B/T	-	-	-	-	-	30	15	
	C413ANSI / CBANSI	-	B/T	2009	2016	-	-	-	30	14	
	C417 / CB	B	B/T	-	-	-	-	-	30	15	
	C417ANSI / CBANSI	-	B/T	2009	2016	-	-	-	30	13	
10 mm Oval	C452	B	B	-	-	-	-	-	30	16	
	C453	B	B	-	-	-	-	-	30	18	
	C453ANSI	-	B	2009	2016	-	-	-	30	17	
	C457	B	B	-	-	-	-	-	30	12	
	C457ANSI	-	B	2009	2016	-	-	-	30	17	
Scaffold Hooks	C714	-	T	1992	-	-	-	-	45	52	
	C714ANSI	-	T	2009	2016	-	-	-	45	50	
	C734	-	T	1992	-	-	-	-	35	52	
	C734ANSI	-	T	2009	2016	-	-	-	35	50	
12 mm Offset	C812 / CB	B	B/T	-	-	-	-	-	45	18	
	C813 / CB	B	B/T	-	-	-	-	-	45	15	
	C813ANSI / CBANSI	-	B/T	2009	2016	-	-	-	45	17	
	C817 / CB	B	B/T	-	-	-	-	-	45	17	
	C817ANSI / CBANSI	-	B/T	2009	2016	-	-	-	45	15	
Klettersteig	C842 / CB	B	B/T	-	-	-	-	-	45	24	
	C843 / CB	B&K	B/T	-	-	-	-	-	45	24	
	C843ANSI / CBANSI	-	B/T	2009	2016	-	-	-	45	23	
	C847 / CB	B&K	B/T	-	-	-	-	-	45	24	
	C847ANSI / CBANSI	-	B/T	2009	2016	-	-	-	45	21	
	C84K2 / CB	B	B/T	-	-	-	-	-	48	26	
	C84K3 / CB	B&K	B/T	-	-	-	-	-	48	26	
	C84K7 / CB	B&K	B/T	-	-	-	-	-	48	26	
12 mm Boa	C852	B&H	B	-	-	-	-	-	40	24	
	C853	B&H&K	B	-	-	-	-	-	40	24	
	C853ANSI	-	B	2009	2016	-	-	-	40	22	
	C857	B&H&K	B	-	-	-	-	-	40	24	
	C857ANSI	-	B	2009	2016	-	-	-	40	22	
Captive Eye	C962	-	T	-	-	-	-	-	45	18	
	C963	-	T	-	-	-	-	-	45	16	
	C963ANSI	-	T	2009	2016	-	-	-	45	16	
	C967	-	T	-	-	-	-	-	45	16	
	SRC67ANSI	-	T	2009	2016	-	-	-	45	16	
MSA Autolock	C96C642	-	B	2009	2016	-	-	-	Class G	55	30

Stainless Steel Connectors

Stainless	S322 / CB	-	B/T	-	-	-	-	-	27	18		
	S322AV / CBAV	-	B/T	-	-	-	-	-	27	18		
	S323 / CB	-	B/T	-	-	-	-	-	27	16		
	S323ANSI / CBANSI	-	-	-	-	-	-	-	27	14		
	S327 / CB	-	B/T	-	-	-	-	-	27	15		
	S327CB / CBANSI	-	B/T	2009	2016	-	-	-	27	13		
Stainless Steel Offset	S812 / CB	-	B/T	-	-	-	-	-	45	18		
	S812AV / CBAV	-	B/T	-	-	-	-	-	45	18		
	S813 / CB	-	B/T	-	-	-	-	-	45	14		
	S813ANSI / CBANSI	-	-	-	-	-	-	-	45	13		
	S817 / CB	-	B/T	-	-	-	-	-	45	14		
	S817ANSI / CBANSI	-	-	-	-	-	-	-	45	13		
	S842 / CB	-	B/T	-	-	-	-	-	40	22		
	S842AV / CBAV	-	B/T	-	-	-	-	-	40	22		
	S843 / CB	-	B/T	-	-	-	-	-	40	21		
	S843ANSI / CBANSI	-	-	-	-	-	-	-	40	20		
	S847 / CB	-	B/T	-	-	-	-	-	40	20		
	S847ANSI / CBANSI	-	-	-	-	-	-	-	40	20		

EN: Warning! Working at height, rock climbing, mountaineering and related activities are inherently dangerous. It is the responsibility of any person using this equipment to learn and practice the proper techniques for use of the equipment for its designated purposes safely and to foresee and take appropriate action in situations where rescue may be required. Even the correct use of equipment and techniques may result in fatal consequences. Medical conditions can affect the safety of the equipment user in normal and emergency use. Any person using this equipment assumes all risks and full responsibility for all damages or injury which may result from the use of it. It is impossible to cover all methods of use. The following instructions and pictograms show some of the common correct and incorrect methods of use; it is impossible to predict them all. There is no substitute for instruction by a trained and competent person.

USER INSTRUCTIONS

IMPORTANT! Please read and understand this information before use, and retain this information for future reference.

General Information

1. These instructions cover the use of DMM Locking Connectors, conforming to one or more international standards. Refer to product list for details. If in doubt please contact your supplier or DMM.

2. This product may be used in conjunction with any appropriate item of Personal Protective Equipment (PPE) relevant to European Union Directive 89/686/EEC / PPE Regulation (EU) 2016/425. It may be acceptable for use in other applications, please consult your supplier. **RISK:** This PPE is designed to protect against falls from height.

3. Immediately before use, visually/functionally inspect to ensure that this product is in a serviceable condition and operates correctly. This inspection should be recorded on the inspection form supplied. We recommend a thorough inspection at least once every 6 months by a competent person (this may be the manufacturer).

4. **Personal Use:** this product may be issued for personal use, and may be used either separately or as part of a system.

5. Lives depend on the use of this equipment. The user should be aware of its history (use, storage, inspection etc.). If this equipment is not for personal use (e.g. used in mountaineering centres), we strongly recommend a systematic approach to record keeping. This should always be carried out by a competent person.

6. **WARNING:** If you are in any doubt about the safe condition of this product, replace it immediately.

7. **WARNING EN362:2004:** If this product has been used to arrest a fall it should be withdrawn from use and destroyed.

8. Ensure that the instructions for other components used in conjunction with this product are complied with. It is the user's responsibility to ensure that he/she understands the correct and safe use of this product.

9. This product is designed for use in normal climatic conditions (-40°C +50°C). It may be suitable for other conditions, please consult your supplier.

